



THERE'S A REASON THEY
— call it “building” —
A REPUTATION.



Notes





TABLE OF CONTENTS

Tools at a Glance	P 4
Cordless Impulse XP Framing Nailer.....	P 8
PowerMaster Plus Framing Nailser.....	P 10
Compact Framing Nailer	P 11
PowerMaster Plus 4" Framing Nailer.....	P 12
SCS200 16 Gauge Standard 1/2" Crown Stapler	P 14
WCS200 16 Gauge Wide 15/16" Crown Stapler	P 15
IMLi200 18 Gauge Brad Nailer	P 16
IMLi200 18 Gauge Short Mag Brad Nailer.....	P 17
IMLi250 16 Gauge Finish Nailer	P 18
16 Gauge Straight Finish Nailer.....	P 19
18 Gauge Brad Nailer	P 21
18 Gauge Brad Nailer/Stapler	P 22
18 Gauge Narrow Soffit Stapler.....	P 24
18 Gauge Narrow Crown Finisher Stapler.....	P 25
US-100 Upholstery/Craft Stapler.....	P 26
HP-100 Headless Pin Nailer.....	P 27
Positive Placement Tool PF250S.....	P 28
FloorMaster Plus™	P 29
FloorMaster Pro™	P 30
Miscellaneous Fasteners.....	P 31



(see page P 8 for more details)

TOOL

CORDLESS IMPULSE XP 30° FRAMING NAILER

Drive 1200 nails per fuel cell
Drive 9000 nails per battery charge
Proven for over 25 years
Durable. Lightweight. Balanced.

PART #: 905800

DESCRIPTION

Weight: 7.2 lbs
Height: 14-1/2"
Length: 12"
Nail Capacity: 40
Range: 2" – 3-1/4"
Shank: .113 - .131

APPLICATIONS

FRAMING, JOISTS,
RAFTERS, SOFFITS,
STAIRS, SHEATHING,
CRATING, FENCES
AND DECKS

**DESIGNED FOR:
FRAMERS & RENOVATORS**



(see page P 10 for more details)

F350-S POWER MASTER+™

Durable construction requires less maintenance.
Proven performer for tough job site work with less jams or misfires
Powerful. Enduring. Reliable.

PART #: 501000

Weight: 8.4 lbs
Height: 13-3/10"
Length: 18"
Nail Capacity: (2 strips) 84
Range: 2" – 3-1/2"
Shank: .113 - .131

FRAMING, JOISTS,
RAFTERS, SOFFITS,
STAIRS, SHEATHING,
CRATING, FENCES
AND DECKS

**DESIGNED FOR:
PROFESSIONAL FRAMERS**



(see page P 11 for more details)

F325R COMPACT FRAMER™

Lightest-framing nailer ever (Only 5.9 lbs)
Smallest Framer Ever (Only 12' long)
Remodel interiors easier
Compact. Lightweight

PART #: 513000

Weight: 5.9 lbs
Height: 12-9/10"
Length: 12-3/10"
Range: 2" – 3-1/4"
Shank: .113 - .131
Magazine Capacity: 44

FRAMING, JOISTS,
RAFTERS, SOFFITS,
STAIRS, SHEATHING,
CRATING, FENCES
AND DECKS

**DESIGNED FOR:
PROFESSIONAL RENOVATORS**



(see page P 12 for more details)

PSN100.1 – 4" FRAMING NAILER 30°

Designed to drive 4" nails
Powerful to drive into engineered lumber
Powerful. Fast. Durable.

PART #: 502900

Weight: 8.9 lbs
Height: 14-1/2"
Length: 19"
Nail Capacity: 84
Range: 2" – 4"
Shank: .113 - .131

LSL, LVL, PSL, AND OSB,
ENGINEERED LUMBER
FOR FRAMING

**DESIGNED FOR:
PROFESSIONAL FRAMERS**

	TOOL	DESCRIPTION	APPLICATIONS
FRAMING STAPLERS	 <p>(see page P 14 for more details)</p>	<p>SCS200 16GA. STANDARD 1/2" CROWN STAPLER</p> <p>Heavy-duty all metal magazine design for increased durability</p> <p>PART #: 515700</p>	<p>Weight: 5.6 lbs Height: 11.7" Length: 15.1" Staple Capacity: 150 Range: 3/4" – 2" Staple Type: 1/2" crown</p> <p>ROOF DECKING, SOFFITS AND FASCIA BOARDS, SHEATHING</p>
	 <p>(see page P 15 for more details)</p>	<p>WCS200 16GA. WIDE 15/16" CROWN STAPLER</p> <p>Drives staples flush in all materials</p> <p>PART #: 515800</p>	<p>Weight: 5.9 lbs Height: 11.7" Length: 15.1" Staple Capacity: 150 Range: 3/4" – 2" Staple Type: 15/16" Crown</p> <p>SOFFITS AND FASCIA BOARDS, SUBFLOOR, SHEATHING, CRATES AND PALLETS</p>
CORDLESS TRIM NAILERS	 <p>(see page P 16 for more details)</p>	<p>IMLi200 – 18GA. BRAD NAILER</p> <p>Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.</p> <p>PART #: 903700</p>	<p>Weight: 4.5 lbs Height: 11-1/2" Length: 11" Nail Capacity: 100 Range: 3/4" – 2" Shank: 18 Gauge</p> <p>CROWN, BASEBOARD MOULDINGS, PANELLING AND CARPENTRY</p>
	 <p>(see page P 17 for more details)</p>	<p>IMLi200 18 GA. SHORT MAG BRAD NAILER</p> <p>Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.</p> <p>PART #: 918150</p>	<p>Weight: 4.25 lbs Height: 11-1/2" Length: 11" Nail Capacity: 70 Range: 5/8" – 2" Shank: 18 Gauge</p> <p>CROWN, BASEBOARD MOULDINGS, PANELLING AND CARPENTRY</p>
	 <p>(see page P 18 for more details)</p>	<p>IMLi250 16GA. STRAIGHT FINISH NAILER</p> <p>Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.</p> <p>PART #: 903800</p>	<p>Weight: 4.6 lbs Height: 11-3/4" Length: 10-1/2" Nail Capacity: 100 Range: 1-1/4" – 2-1/2" Shank: 16 ga. Straight</p> <p>DOOR AND WINDOW TRIM, CASING, CROWN AND BASEBOARD MOULDING</p>



(see page P 19 for more details)

TOOL

**T250S F16P - 16GA.
STRAIGHT FINISH NAILER**
Best in class ergonomics
Reliable and Durable
Low Maintenance

PART #: 515500

DESCRIPTION

Weight: 3.90 lbs
 Height: 11.6"
 Length: 12.3"
 Nail Capacity: 100 (2 strips)
 Range: 1" – 2-1/2"
 Nail Type: 16 Ga.
 (Smooth/Galvanized)

APPLICATIONS

**RESIDENTIAL:
WINDOW AND DOOR
TRIM/FINISH APPLICATIONS,
CARPENTRY, AND PANELLING**



(see page P 21 for more details)

**P18-200 18 GA.
BRAD NAILER**
Lightweight and well balanced
No mar tip
Easy to access corners

PART #: P18-200

Weight: 2.9 lbs.
 Height: 9-1/2"
 Length: 10-1/4"
 Nail Capacity: 100
 Range: 5/8" – 2"
 Nail Type: 18 ga. –
 Smooth, Galvanized
 Type: 18 ga.

**WINDOWS, DOORS,
FURNITURE, TRIM
APPLICATIONS**



(see page P 22 for more details)

**P18-FS200 18 GA.
BRAD NAILER/STAPLER**
Lightweight and well balanced
No mar tip
Easy to access corners

PART #: P18-FS200

Weight: 2.9 lbs.
 Height: 9-1/2"
 Length: 10-1/4"
 Nail Capacity: 100
 Range: 5/8" – 2" brad nails
 and 5/8" – 1-1/2" staples
 (3/16" crown)
 Type: 18 ga. & 3/16

**WINDOWS, DOORS,
FURNITURE, TRIM
APPLICATIONS**



(see page P 24 for more details)

**N18-125 – 1-1/4"
NARROW SOFFIT STAPLER**
**Specifically designed for soffit
installation with long narrow
nosepiece for tight spots.**

PART #: N18-125

Weight: 2.5 lbs.
 Height: 9"
 Length: 9-1/4"
 Staple Capacity: 100
 Range: 3/4" – 1 1/4"
 Staple Type: 3/16" crown
 GSN18

**TRIM/FINISH, PLYWOOD,
SOFFITS/FACIAS,
UNDERLAYMENT
APPLICATIONS**



(see page P 25 for more details)

**N18 150 – 1-1/2"
NARROW CROWN
FINISH STAPLER**
Heavy Duty for long life
4000 Shots per batt. charge

PART #: N18-150

Weight: 2.8 lbs.
 Height: 9-3/4"
 Length: 11-1/2"
 Staple Capacity: 100
 Range: 3/4" – 1 1/2"
 Staple Type: 3/16" crown
 GSN18

**TRIM/FINISH, PLYWOOD,
SOFFITS/FACIAS,
UNDERLAYMENT
APPLICATIONS**

	TOOL	DESCRIPTION	APPLICATIONS
LITE GAUGE FASTENING STAPLERS	 <p>(see page P 26 for more details)</p>	<p>US-100 – UPHOLSTERY/ CRAFT STAPLER</p> <p>Easy load magazine 5 Staples/second</p> <p>PART #: US-100</p>	<p>Weight: 2.00 lbs. Height: 9-1/2" Length: 12-1/2" Staple Capacity: 100 Range: 3/8" – 9/16" Staple Type: 22 ga. Upholstery</p> <p>UPHOLSTERY, CRAFTS, LIGHT PANELING AND HOME PROJECT APPLICATIONS</p>
	 <p>(see page P 27 for more details)</p>	<p>23GA HEADLESS PIN NAILER</p> <p>Lightweight and compact No mar tip and nail lock out</p> <p>PART #: HP100</p>	<p>Weight: 1.20 lbs. Height: 9-1/4" Length: 7-3/4" Staple Capacity: 100 Range: 1/2" – 1-1/2" Staple Type: 23 ga.</p> <p>FINE WOODWORKING AND TRIM WORK</p>
JOIST HANGERS	 <p>(see page P 28 for more details)</p>	<p>2.5" POSITIVE PLACEMENT® METAL CONNECTOR NAILER PF250S</p> <p>Dependable, Lightweight, Compact and Accurate</p> <p>PART #: 511800</p>	<p>Weight: 7.8 IBS Height: 14" Length: 17.4" Nail Capacity: 55-60 Nails (2 strips) Nail Range: .131" to .162" (Shank) Magazine Angle: 30 Degrees Nail Type: 1-1/2" to 2-1/2" Positive Placement Hanger Nails – Brite and Galvanized Air req: 80-120 PSI</p> <p>JOIST HANGERS</p>
FLOORING	 <p>(see page P 29 for more details)</p>	<p>FLOORMASTER PLUS™ 2 IN 1 FLOORING NAILER/ STAPLER</p> <p>Drives staples and cleats to meet flooring manufacturers fastening specifications</p> <p>PART #: F2N1-200</p>	<p>Weight: 10.4 lbs Height: 18" Length: 16" Flooring Fasteners: 15ga staples & 16ga L-cleats Fastener Lengths: 2", 1-3/4, 1-1/2"</p> <p>3/4" HARDWOOD FLOORING</p>
	 <p>(see page P 30 for more details)</p>	<p>FLOORMASTER PRO™ NAILER/STAPLER 2 IN 1 COMBO</p> <p>Professional Grade Durability & Performance</p> <p>PART #: FNS-200</p>	<p>Weight: 11 lbs Height: 21-5/8" Length: 18" Flooring Fasteners: 15-1/2ga staples & 16ga L-Cleats Fastener Lengths: 2", 1-3/4, 1-1/2"</p> <p>3/4" SOLID AND ENGINEERED FLOORING</p>



IM325XP Cordless Impulse XP Framing Nailer

*Portable freedom
on the jobsite
without hoses or
compressors*



INCLUDES

Cordless Li-ion Framing Nailer, Model IM325XP
Rechargeable 7.4V Li-ion battery
Li-ion battery charger
Rugged carrying case
Owner's manual
Safety glasses
5/32" Hex Wrench

DESCRIPTION/SUGGESTED SPECIFICATIONS

Cordless Impulse XP Framing Nailer—

IT'S MORE THAN A NAILER, IT'S A NAILING SYSTEM THAT GETS THE JOB DONE RIGHT.

The Paslode Lithium Ion cordless Impulse nailer has provided framers and renovators the ability to wood frame without air hoses for over 25 years. New Li-ion battery technology drives 50% more nails per charge. 2-times faster charge time; 2 minute quick charge drives up to 200 nails. Tool free depth of drive adjustment, non slip grip, dual position utility hook, sequential operation triggers.

LIGHTWEIGHT



QUICK LOADING



EASY ACCESS



ADVANTAGES

- Portable, freedom on the jobsite without hoses or compressors
- Heavy-duty rafter/belt hook for taking jobsite abuse
- Non-slip grip provides comfort and reduces hand fatigue
- Tool free depth-of-drive nail adjustment changes nail depth in an instant – even while wearing gloves
- Nail lockout feature prevents blank driving
- Compact size fits between 16" o.c. studs, joists and roof trusses
- Li-ion battery – provides 50% longer run time (up to 9,000 nails per charge) than NiCd battery
- 1-hour Full Charge; 2-minute Quick Charge for Up to 200 shots
- Lightweight – 7.2 lbs. including battery for better comfort and control
- Works in cold temperature down to -10°C

SPECIFICATIONS

Part No. 905800

Weight: 7.2 lbs
Height: 14-1/2"
Length: 12"
Width: 4"
Speed: 2-3 nails per second
Nail Capacity: 40

Range: 2" – 3-1/4"

Shank: .113 – .131

Nail Angle: 30°

Fuel Type: Spare Framing Fuel

Nails per Fuel Cell: Approximately 1200

Fuel life: 21 months from date of manufacture

Battery Life: 9000 nails per charge

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts: • Motor Housing, Cap and Grille • Trigger • Handle Halves and Actuator • Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts: • Bumper • O-Rings • Driver Blades • Seal Rings

SELECTION CHART

Pro-Strip RoundDrive Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QUANTITY PER MASTER	QUANTITY PER SKID
COATING TYPE: BRITE								
2"	0.113	Smooth	Roundrive	Brite	097385	6,500	1	80
2"	0.113	Ring	Roundrive	Brite	650273	5,500	1	80
2-3/8"	0.113	Smooth	Roundrive	Brite	50238	5 Strips	10	-
2-3/8"	0.113	Smooth	Roundrive	Brite	404238	1,000	4	-
2-3/8"	0.113	Smooth	Roundrive	Brite	097394	5,000	1	96
2-3/8"	0.113	Ring	Roundrive	Brite	097397	5,000	1	96
3"	0.120	Smooth	Roundrive	Brite	097971	3,000	1	96
3"	0.120	Ring	Roundrive	Brite	097973	3,000	1	96
3-1/4"	0.120	Smooth	Roundrive	Brite	50314	5 Strips	1	125
3-1/4"	0.120	Smooth	Roundrive	Brite	404314	1,000	4	-
3-1/4"	0.120	Smooth	Roundrive	Brite	404058	3,000	1	96
3-1/4"	0.131	Smooth	Roundrive	Brite	650839	2,500	1	96
3-1/4"	0.131	Ring	Roundrive	Brite	097978	2,500	1	96
3-1/2"	0.120	Smooth	Roundrive	Brite	404855	2,500	1	96
3-1/2"	0.131	Smooth	Roundrive	Brite	097987	2,500	1	96
4"	0.131	Smooth	Roundrive	Brite	2X0788	2,500	1	96
COATING TYPE: HOT DIPPED								
2"	0.113	Ring	Offset Oval	Hot Dipped	403389	2,500	1	150
2-3/8"	0.113	Ring	Offset Oval	Hot Dipped	404856	2,500	1	150
3"	0.120	Ring	Offset Oval	Hot Dipped	404857	1,500	1	150
3-1/4"	0.120	Ring	Offset Oval	Hot Dipped	50314G	5 Strips	6	-
3-1/4"	0.120	Ring	Offset Oval	Hot Dipped	404858	1,500	1	150

Pro-Strip RoundDrive Fuel/Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	FUEL CELLS PER PACK
2-3/8"	0.113	Smooth	Roundrive	Brite	1238FN	1,000	1
2-3/8"	0.113	Smooth	Roundrive	Brite	3238FN	3,000	3
3"	0.120	Smooth	Roundrive	Brite	3300FN	3,000	3
3-1/4"	0.120	Smooth	Roundrive	Brite	1325FN	1,000	1
3-1/4"	0.120	Smooth	Roundrive	Brite	3325FN	3,000	3

See Page P 13 for additional framing nails that work with this tool.

- ICC-ES Recognized, ESR-3072
- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Framing
Joists and rafters
Soffits
Stairs
Sheathing
Crating
Fences and decks

TOOL ACCESSORIES



Part No. 902513
All Season Orange Fuel Cell



Part No. 902654C
Li Ion Battery



Part No. 902667C
Lithium Battery Charger



Part No. 901252
Cordless No mar tip



Part No. 401482
Impulse Oil



Part No. 219086
Degreaser



PF-350S PowerMaster Plus Framing Nailer

*Durability,
Balance and
Versatility
for all jobs*



SEE PAGE P 13 FOR
FRAMING NAILS SELECTION CHART

INCLUDES

- PowerMaster™ Plus Pneumatic Framing Nailer
- Bump fire trigger
- Hex wrench (on tool)
- Safety glasses
- Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus Framing Nailer—

DESIGNED FOR PROFESSIONAL FRAMERS

Heavy-duty jobs require a heavy-duty nailer. That's why the pros turn to the proven performance, durability and driving power, only a Paslode pneumatic framing nailer can provide. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- Frame full walls faster. Heavy duty power.
- Reliable performance that saves time with less maintenance.
 - Durable construction requires less maintenance.
 - Proven performer for tough job site work with less jams or misfires
 - Compact size fits between 16" o.c. studs, joists and rafters.
- Soft grip handle for comfort
- Bolt-on end plug for easier service
- Depth of drive on the tool rather than the compressor saves time and energy
- Rafter hook, moves out of the way when not in need
- Adjustable air deflector cap

APPLICATIONS



- | | |
|--------------------|------------------|
| Framing | Sheathing |
| Joists and rafters | Crating |
| Soffits | Fences and decks |
| Stairs | |

SPECIFICATIONS

Part No. 501000

- Weight: 8.4 lbs
- Height: 13-3/10"
- Length: 18"
- Speed: 12 nails per second*, sequential or selectable operation
- Nail Capacity: 2 strips (up to 84)
- Nail Range: 2" – 3.5" in length, .113" – .131" shank diameters

- Nail Angle: 30°
- Nail Type: Paslode RoundDrive® Offset Full Head
- Air Req./100p.s.i. (6.9 bar): .082/cycle
- Op. Pres. p.s.i (bar): 80 – 120 (5.5 – 8.3)
- Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts



F325R Compact Framing Nailer

*Lightest weight
framer ever*



SEE PAGE P 13 FOR
FRAMING NAILS SELECTION CHART

INCLUDES

Compact 30° Framing Nailer
Safety glasses
Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

Compact Framing Nailer—

DESIGNED FOR RENOVATORS

With this nailing system, you'll have any interior remodeling job done in no time. Get the access and maneuverability you need in tight spaces with this lightweight yet powerful pneumatic nailing system. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

PROFESSIONAL



LIGHTWEIGHT



EASY ACCESS



ADVANTAGES

- Remodel interiors easier. Lightest weight framer ever.
 - Remodel Interiors Easier
 - First pneumatic nailer made especially with remodeler's needs in mind
 - Fits easily into the tightest spaces such as between 16" o.c. studs
- Great maneuverability to work comfortably overhead
- Lightest-framing nailer ever made: 5.9 lbs
- Quick 2-step nail strip reload
- Soft grip handle for comfort
- Works in bump mode for speed on jobsite

APPLICATIONS



Framing

Joists and rafters

Soffits

Stairs

Sheathing

Crating

Fences and decks

SPECIFICATIONS

Part No. 513000

Weight: 5.9 Pounds

Height: 12-9/10"

Width: 4-3/10"

Length: 12-3/10"

Fastener Range: 2" – 3 1/4"

Shank: .113 - .131

Magazine Capacity: 44

Op. Pres. p.s.i (bar): 90 – 120



PowerMaster Plus 4" Framing Nailer

Proven durability and reliability



SEE PAGE P 13 FOR FRAMING NAILS SELECTION CHART

INCLUDES

- PowerMaster Plus 4" Framing Nailer
- Safety glasses
- Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus 4" —

DESIGNED FOR TIMBER FRAMERS

The F400S is the PowerMaster Plus framing nailer with an extended power and driver blade for 4" applications.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- PowerMaster Plus Design - Proven durability and reliability
- Ergonomic Design - Centre of gravity is closer to the trigger, providing better balance.
- Versatile - Drives a variety of nails from 1-1/2" to 4" in length.
- Durable And Reliable - Rugged design will stand up to the demands of the job in any kind of weather.

APPLICATIONS



LSL, LVL, PSL, and OSB

Wall Sheathing

Framing

Floor Decking

Roof

SPECIFICATIONS

Part No. 502900

Weight: 8.9 lbs

Height: 14-1/2"

Length: 19"

Nail Capacity: 84

Range: 2" — 4"

Shank: .113 — .131

Back of tool to Nosepiece: 14.5"

Magazine Angle: 30°

Nail Type: 30° Paper Tape, full head/clipped

OP. Pres. p.s.i. (bar): 80 — 120 (5.5 — 8.3)

Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.

SELECTION CHART

Pro-Strip RoundDrive Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	HEAD STYLE	COATING	PRODUCT NUMBER	NAILS PER PACK	QUANTITY PER MASTER	QUANTITY PER SKID
COATING TYPE: BRITE								
2"	0.113	Smooth	Roundrive	Brite	097385	6,500	1	80
2"	0.113	Ring	Roundrive	Brite	650273	5,500	1	80
2-3/8"	0.113	Smooth	Roundrive	Brite	50238	5 Strips	10	-
2-3/8"	0.113	Smooth	Roundrive	Brite	404238	1,000	4	-
2-3/8"	0.113	Smooth	Roundrive	Brite	097394	5,000	1	96
2-3/8"	0.113	Ring	Roundrive	Brite	097397	5,000	1	96
3"	0.120	Smooth	Roundrive	Brite	097971	3,000	1	96
3"	0.120	Ring	Roundrive	Brite	097973	3,000	1	96
3-1/4"	0.120	Smooth	Roundrive	Brite	50314	5 Strips	1	125
3-1/4"	0.120	Smooth	Roundrive	Brite	404314	1,000	4	-
3-1/4"	0.120	Smooth	Roundrive	Brite	404058	3,000	1	96
3-1/4"	0.131	Smooth	Roundrive	Brite	650839	2,500	1	96
3-1/4"	0.131	Ring	Roundrive	Brite	097978	2,500	1	96
3-1/2"	0.120	Smooth	Roundrive	Brite	404855	2,500	1	96
3-1/2"	0.131	Smooth	Roundrive	Brite	097987	2,500	1	96
4"	0.131	Smooth	Roundrive	Brite	2X0788	2,500	1	96
COATING TYPE: HOT DIPPED								
2"	0.113	Ring	Offset Oval	Hot Dipped	403389	2,500	1	150
2-3/8"	0.113	Ring	Offset Oval	Hot Dipped	404856	2,500	1	150
3"	0.120	Ring	Offset Oval	Hot Dipped	404857	1,500	1	150
3 1/4"	0.120	Ring	Offset Oval	Hot Dipped	50314G	5 Strips	6	-
3-1/4"	0.120	Ring	Offset Oval	Hot Dipped	404858	1,500	1	150

Also works with Cordless Impulse Framing Nailer (see page P 8)

- ICC-ES Recognized, ESR-3072
- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153

PRO-STRIP ROUNDRIE NAILS FOR USE WITH



POWERMASTER PLUS



COMPACT FRAMER



POWERMASTER PLUS 4" FRAMER



CORDLESS IMPULSE XP
FRAMING NAILER





SCS200 16 Ga. Standard 1/2" Crown Stapler

Heavy-duty all metal
magazine design for
increased durability



INCLUDES

- SCS200 Crown Stapler
- Pneumatic Lubricating Oil
- Safety glasses
- Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

SCS200 16Ga. Standard 1/2" Crown Stapler

WITH THE RIGHT STAPLER AND STAPLES, YOU'LL HAVE THE JOB DONE IN NO TIME.

The new Paslode 16ga standard crown stapler is built for professional framers with speed and power that will increase jobsite productivity by allowing you to work quickly, never having to pull out your hammer to finish off staples. this durable stapler will hold up to any jobsite conditions or high volume industrial usage..

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- Lightweight: Only 5.6 lbs
- Quick-Clear Nose: For easy jam clearance
- Quick Release Follower Tab: Makes reloading fast
- Staple Capacity: Up to 150 staples
- Staple Range: 3/4" – 2"

SELECTION CHART

16 Gauge Standard Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1"	1/2"	Chisel	16	Galvanized	OT5242	16,500
1-1/4"	1/2"	Chisel	16	Galvanized	OT5238	13,500
1-1/2"	1/2"	Chisel	16	Galvanized	OT2695	10,500
1-3/4"	1/2"	Chisel	16	Galvanized	OT2250	9,000
2"	1/2"	Chisel	16	Galvanized	OT2258	7,500

APPLICATIONS



- Roof Decking
- Soffits and Fascia Boards
- Sheathing

SPECIFICATIONS

Part No. 515700

Weight: 5.6 lbs

Height: 11.7"

Width: 3/4"

Length: 15.1"

Op. Pres. 80 to 120 p.s.i. (5.5 to 8.3 bars)

Staple Length: 3/4" – 2"

Staple Diameter: 16 gauge

ONE-YEAR FULL WARRANTY A one-year warranty will apply to all parts, except those which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all housing and cap assembly castings.



WCS200 16 Ga. Wide 15/16" Crown Stapler

*Drives staples flush
in all materials*



INCLUDES

WCS200 Wide 15/16" Crown Stapler
Pneumatic Lubricating Oil
Safety glasses
Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

WCS200 16Ga. Wide 15/16" Crown Stapler

RELIABLE. DURABLE. POWERFUL.

Tested and proven to reliably hold up to any application on most extreme jobsites. By using Paslode staples, you'll have fewer jams, fewer misfires and faster loading, only a Paslode stapling system can deliver.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- **Lightweight:** only 5.9 lbs
- **Quick-Clear Nose:** For easy jam clearance
- **Quick Release Follower Tab:** Makes reloading fast
- **Staple Capacity:** Up to 150 staples
- **Staple Range:** 3/4" – 2"
- **Tool-free Adjustable Depth of Drive:** Easily adjust depth for consistency in any material

SELECTION CHART

16 Gauge Wide Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
7/8"	15/16"	Chisel	16	Galvanized	404069	9,000
1-1/2"	15/16"	Chisel	16	Galvanized	0T2855	10,500

APPLICATIONS



Soffits and Fascia Boards
Subfloor
Sheathing
Crates and Pallets

SPECIFICATIONS

Part No. 515800

Weight: 5.9 lbs

Height: 11.7"

Width: 3/4"

Length: 15.1"

Op. Pres. 80 to 120 p.s.i. (5.5 to 8.3 bars)

Staple Length: 3/4" – 2"

Staple Diameter: 16 gauge

ONE-YEAR FULL WARRANTY A one-year warranty will apply to all parts, except those which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all housing and cap assembly castings.

IMLi200 18 Gauge Brad Nailer

*Lightweight and
well balanced*



TOOL ACCESSORIES

- Part No. 902654C** Lithium Ion 7.4v battery
- Part No. 902667C** Lithium Ion Battery Charger
- Part No. 219236** 3 Pack of No Mar Tips
- Part No. 219086** Degreaser Cleaner
- Part No. 401482** Impulse Oil
- Part No. 650039** Universal Trim Fuel Cell (4 pk)

INCLUDES

- IMLi200 18 Ga Brad Nailer
- Rugged Carrying Case
- Rechargeable Battery with Charger
- Safety glasses
- Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Gauge Brad Nailer—

WE'VE GOT THE FACTS NAILED.

When you need precision in tight spaces, reach for the lightweight Paslode Cordless Finishing Nailing System. It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away

POWERFUL




PRECISE



PRODUCTIVE



PENNIES PER SHOT



ADVANTAGES

- Li-Ion for 50% more shots (12,000) per charge
- Quick charge to 80% in 30 minutes
- New battery standby position conserves charge
- New easier depth of drive thumbwheel
- New reversible belt hook
- 8% lighter — 4.5 lbs with battery (compared with Ni-Cad battery)

SELECTION CHART

18 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.048	Chisel	18	Galvanized	FFP-118112	1,000
2"	0.048	Chisel	18	Galvanized	FFP-118002	1,000

See Page P 23 for additional finish nails that work with this tool.

APPLICATIONS



Crown and baseboard
mouldings
Panelling
Carpentry

SPECIFICATIONS

Part No. 903700

Weight: 4.5 lbs
Height: 11-1/2"
Length: 11"

Nail Capacity: 100
Nail Range: 5/8" — 2"
Nail Type: 18 ga

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts:

• Motor Housing, Cap and Grille • Handle Halves and Actuator • Trigger • Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts: • Bumper • Driver Blades • O-Rings • Seal Rings



IMLi200 18 Ga. Short Mag Brad Nailer

*Made to Fit in
Tight Spaces*



TOOL ACCESSORIES

- Part No. 902654C Lithium Ion 7.4v battery
- Part No. 902667C Lithium Ion Battery Charger
- Part No. 219236 3 Pack of No Mar Tips
- Part No. 219086 Degreaser Cleaner
- Part No. 401482 Impulse Oil
- Part No. 650039 Yellow Trim Fuel Cell (4 pk)

INCLUDES

- IMLi200 18 Ga Short Mag Brad Nailer
- Rugged Carrying Case
- Rechargeable Battery with Charger
- Safety glasses
- Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Ga. Cordless Li-ion Brad Nailer - 1 Strip

MANEUVERABLE. PRECISE. LIGHTWEIGHT.

The NEW Paslode 18 Ga. Cordless Li-ion Brad Nailer is the ideal nailer for all of your trim projects. This tool has superior access to tight spaces so you are able to fasten in areas that aren't easily accessible. This consistent nailer makes your job easier than ever, driving each nail flush into all types of trim. Finally, weighing 4.25 lbs., this is the lightest Cordless Brad Nailer on the market.

POWERFUL




PRECISE



PRODUCTIVE



PENNIES PER SHOT



ADVANTAGES

- 7.4-volt Li-ion battery drives up to 12,000 s/b nails per charge
- 1-1/2 hour full charge; 2-minute quick charge for up to 200 extra shots
- Battery stand-by position secures battery in off position to conserve battery power
- Reversible belt hook – Easily adjusts and keeps both hands free
- Tool free depth of drive is easy to adjust, even with gloves on

SELECTION CHART

18 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.048	Chisel	18	Galvanized	FFP-118112	1,000
2"	0.048	Chisel	18	Galvanized	FFP-118002	1,000

See Page P 23 for additional finish nails that work with this tool.

APPLICATIONS



Window Castings
Baseboards moldings
Decorative trim

SPECIFICATIONS

Part No. 918150

Weight: 4.25 lbs
Height: 11-1/2"
Length: 11"
Nail Capacity: 70

Nail Range: 5/8" – 2"
Nail Type: 18 ga
Warranty: 1-year limited

IMLi250 16 Gauge Finish Nailer

*Lightweight and
well balanced*



TOOL ACCESSORIES

- Part No. 902654C** Lithium Ion 7.4v battery
- Part No. 902667C** Lithium Ion Battery Charger
- Part No. 219236** 3 Pack of No Mar Tips
- Part No. 219086** Degreaser Cleaner
- Part No. 401482** Impulse Oil
- Part No. 650039** Universal Trim Fuel Cell (4 pk)

INCLUDES

- IMLi250 16 Ga Straight Finish Nailer
- Rugged Carrying Case
- Rechargeable Battery with Charger
- Safety Glasses
- Owner's Manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

16 Gauge Straight Cordless Finish Nailer— GREAT MANEUVERABILITY.

It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away.

POWERFUL



PRECISE



PRODUCTIVE



PENNIES PER SHOT



ADVANTAGES

- Powerful precision – Finish right the first time.
- Li-ion Battery – Drives up to 12,000 nails per charge
- Lightweight – Only 4.6 pounds for added comfort and control
- Use Paslode Universal Trim Fuel – Drives approx. 1,000 nails
- Battery Standby Position – Conserves battery power
- 1 Hour Rapid Charger – 80% charge in 20 min

SELECTION CHART

16 Gauge Fuel and Finish Nail Packs

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1 1/2"	0.063	Chisel	16	Galvanized	FFP-116112	1,000
2"	0.063	Chisel	16	Galvanized	FFP-116002	1,000

See Page P 20 for additional finish nails that work with this tool.

APPLICATIONS



- Door and window trim
- Casing
- Crown and baseboard moulding

SPECIFICATIONS

Part No. 903800

- Weight: 4.6 lbs
- Height: 11-3/4"
- Length: 10-1/2"

- Nail Capacity: 100
- Nail Range: 1" - 2-1/2"
- Nail Type: 16 ga Straight

ONE-YEAR LIMITED WARRANTY A one-year warranty will apply to all parts, except those listed below as normal wearing parts, or parts which are specifically covered by an extended warranty.

FIVE-YEAR EXTENDED LIMITED WARRANTY A five-year warranty will apply to all molded nylon parts:

- Motor Housing, Cap and Grille
- Handle Halves and Actuator
- Trigger
- Magazine Parts

90-DAY LIMITED WARRANTY A 90-day warranty applies to the following parts, which are considered normal wearing parts:

- Bumper
- Driver Blades
- O-Rings
- Seal Rings

T250S F16P 16 Gauge Finish Nailer

*Best in Class
Ergonomics*



INCLUDES

T250S F16P – 16 Gauge Finish Nailer
1/4" air fitting
Rugged Carrying Case
Owner's Manual
Safety Glasses

DESCRIPTION/SUGGESTED SPECIFICATIONS

T250S F16P – 16 Gauge Finish Nailer—

LIGHTWEIGHT. HIGH PERFORMANCE. LOW MAINTENANCE.

The Paslode 16 Ga. Pneumatic Finish Nailer has a best-in-class design that allows for comfort in all applications. This is a reliable and durable tool you can trust to keep up with you. The oil-free design allows for long term, maintenance-free operation which reduces cleanup time and associated costs.

LIGHTWEIGHT



DEPENDABLE



OIL FREE



ADVANTAGES

- Best in class ergonomics – Designed with enhanced features to optimize balance, maximize comfort, reduce fatigue and increase productivity
- Reliability and durability – Proven performance that saves you time and can keep up with you
- Low maintenance – Oil-free design allows for long term, maintenance-free operation which reduces cleanup time and associated costs

APPLICATIONS



Window and door trim/finish applications
Carpentry
Panelling

SPECIFICATIONS

Part No. 515500

Weight: 3.9 lbs

Height: 11.6"

Length: 12.3"

Nail Capacity: 100 (2 strips)

Nail Range: 1" – 2-1/2"

Magazine Angle: Straight Collation

Nail Type: 16 Ga. (Smooth/Galvanized)

Op. Pressure P.S.I (Bar): 80-120 p.s.i

Warranty: 5 Year limited warranty

SELECTION CHART

16 Gauge Finish Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1"	0.063	Chisel	16	Galvanized	095203	5,000
1-1/4"	0.063	Chisel	16	Galvanized	095205	5,000
1-1/2"	0.063	Chisel	16	Galvanized	095257	4,000
1-3/4"	0.063	Chisel	16	Galvanized	095435	2,500
2"	0.063	Chisel	16	Galvanized	095436	2,500
2-1/2"	0.063	Chisel	16	Galvanized	090025	2,500
MULTI	0.063	Chisel	16	Galvanized	116000	2,000
1"	0.063	Chisel	16	Galvanized	116001	1,000
1-1/4"	0.063	Chisel	16	Galvanized	116114	1,000
1-1/2"	0.063	Chisel	16	Galvanized	116112	1,000
1-3/4"	0.063	Chisel	16	Galvanized	116134	1,000
2"	0.063	Chisel	16	Galvanized	116002	1,000
2-1/4"	0.063	Chisel	16	Galvanized	400601	2,500
2-1/2"	0.063	Chisel	16	Galvanized	116025	1,000

- ICC-ES Recognized, ESR-3072
- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153



16 GAUGE FINISH NAILS FOR USE WITH



T250S F16P – 16 GAUGE FINISH NAILER



IMLi250 – 16 GAUGE FINISH NAILER

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/
Antifreeze



Part No. 650039
Universal Trim Fuel Cell
(4 Pk)

P18-200 18 Gauge Brad Nailer

*Jobsite tough
all metal housing
and magazine*



SEE PAGE P 22 FOR
18 GAUGE NAILS SELECTION CHART

INCLUDES

P18-200 18 Gauge Brad Nailer
3 no mar tips
Air fitting
Oil
Safety glasses
Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-200 18 Gauge Brad Nailer —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout
- Quick-release nose
- 360° adjustable exhaust
- 5/8" to 2" nails

APPLICATIONS

Windows
Doors
Furniture
Trim applications

SPECIFICATIONS

Part No. P18-200

Weight: 2.9 lbs
Height: 9.5"
Length: 10.25"
Nail Capacity: 100
Nail Range: 5/8" – 2"
Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth, Galvanized
OP. Pres. p.s.i. (bar): 80-120
Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts



P18-FS200 18 Gauge Brad Nailer/ Stapler

*Paslode driving
power with
the features
contractors
demand*



SEE PAGE P 24 FOR
18 GA. 1/4" CROWN STAPLES

INCLUDES

P18-FS200 18 Gauge Brad Nailer/Stapler
3 no mar tips
Air fitting
Oil
Safety glasses
Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-FS200 18 Gauge Brad Nailer/Stapler — BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout
- Quick-release nose
- 360° adjustable exhaust
- 5/8" to 2" Nails, 5/8" to 1-1/2" staples

APPLICATIONS

Windows
Doors
Furniture
Trim applications

SPECIFICATIONS

Part No. P18-FS200

Weight: 2.9 lbs
Height: 9.5"
Length: 10.25"
Nail Capacity: 100
Nail Range: 5/8" – 2" brad nails and
5/8" – 1-1/2" staples (1/4" crown)
Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth,
Galvanized Nails and 1/4" Crown Staples
OP. Pres. p.s.i. (bar): 80-120
Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.

SELECTION CHART

18 Gauge Finish Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
MULTI	0.048	Chisel	18	Galvanized	118000	2,000
1"	0.048	Chisel	18	Galvanized	118001	1,000
2"	0.048	Chisel	18	Galvanized	118002	1,000
3/4"	0.048	Chisel	18	Galvanized	118034	1,000
5/8"	0.048	Chisel	18	Galvanized	118058	1,000
1-1/2"	0.048	Chisel	18	Galvanized	118112	1,000
1-1/4"	0.048	Chisel	18	Galvanized	118114	1,000
1-3/4"	0.048	Chisel	18	Galvanized	118134	1,000
1"	0.048	Chisel	18	Galvanized	950001	3,000
2"	0.048	Chisel	18	Galvanized	950002	3,000
3/4"	0.048	Chisel	18	Galvanized	950034	6,000
1-1/2"	0.048	Chisel	18	Galvanized	950112	3,000
1-1/4"	0.048	Chisel	18	Galvanized	950114	3,000
1-3/4"	0.048	Chisel	18	Galvanized	950134	3,000

- ICC-ES Recognized, ESR-3072
- Approved for use in all pressure treated lumber such as ACQ and MCQ
- Polymer coating on nail head reduces staining and streaking by 80% compared to traditional hot dipped galvanized nails
- IRC R319.3 code approved for use in pressure treated lumber in accordance with ASTM A 153



18 GAUGE FINISH NAILS FOR USE WITH



P18-200 –
18 GAUGE BRAD NAILER



P18-FS200 –
18 GAUGE BRAD NAILER/STAPLER



IMLI200 – 18 GAUGE
FINISH NAILER

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/
Antifreeze



Part No. 650039
Universal Trim Fuel Cell
(4 Pk)

N18-125 1-1/4" Narrow Soffit Stapler

**Adjustable Exhaust
– Maintains a
Cleaner Working
Environment**



INCLUDES

N18-125 – 1-1/4" Narrow Soffit Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-125 – 1-1/4" Narrow Soffit Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL



EASY ACCESS



PROFESSIONAL



ADVANTAGES

- Ergonomically Balanced and Lightweight – To reduce arm fatigue.
- Quick Clear Nose Piece – to reduce down time on the job if a jam should occur.
- Narrow Nose Piece – Allows the tool to fit into tight corners.
- Magnesium Metal Housing – Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1/2"	1/4"	Chisel	18	Galvanized	180121	1,000
3/4"	1/4"	Chisel	18	Galvanized	180341	1,000
1"	1/4"	Chisel	18	Galvanized	180011	1,000
1"	1/4"	Chisel	18	Galvanized	140015	5,000
1-1/4"	1/4"	Chisel	18	Galvanized	181141	1,000
1-1/4"	1/4"	Chisel	18	Galvanized	141145	5,000

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-125

Weight: 2.5 lbs

Height: 9"

Length: 9-1/4"

Nail Capacity: 100

Nail Range: 3/4" - 1-1/4"

Nail Type: GSN 18, 3/16 inch (1/4" crown)

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.



1-1/2" Narrow Crown Finish Stapler

*Ergonomically
Balanced and
Lightweight –
To Reduce
Arm Fatigue*



INCLUDES

N18-150 – 1-1/2" Narrow Crown Finish Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-150 - 1-1/2" Narrow Crown Finish Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL



PRECISE



PROFESSIONAL



ADVANTAGES

- Adjustable Exhaust – Maintains a cleaner working environment.
- Quick Clear Nose Piece – to reduce down time on the job if a jam should occur.
- Narrow Nose Piece – Allows the tool to fit into tight corners.
- Magnesium Metal Housing – Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
1/2"	1/4"	Chisel	18	Galvanized	180121	1,000
3/4"	1/4"	Chisel	18	Galvanized	180341	1,000
1"	1/4"	Chisel	18	Galvanized	180011	1,000
1"	1/4"	Chisel	18	Galvanized	140015	5,000
1 1/4"	1/4"	Chisel	18	Galvanized	181141	1,000
1 1/4"	1/4"	Chisel	18	Galvanized	141145	5,000
1 1/2"	1/4"	Chisel	18	Galvanized	141125	5,000

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-150

Weight: 2.8 lbs

Height: 9-3/4"

Length: 11-1/2"

Nail Capacity: 100

Nail Range: 3/4" - 1-1/2"

Nail Type: GSN 18, 3/16 inch (1/4" crown)

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.



US-100 Upholstery/ Craft Stapler

*Easy-load
Magazine*



DESCRIPTION/SUGGESTED SPECIFICATIONS

US-100 Upholstery/Craft Stapler—

LONG NARROW NOSEPIECE FOR TIGHT SPOTS

Lightweight - At only 2 lbs this tool is very easy to handle and decreases operator fatigue. Heavy-duty driver blade.

FAST



PRECISE



QUICK LOAD



ADVANTAGES

- Drives 3/8" - 9/16" upholstery staples.
- Fast - Shoots 5 staples per second

SELECTION CHART

22 Gauge Upholstery Staples

LENGTH	CROWN SIZE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
3/8"	3/8"	Chisel	22	Galvanized	422038	4,000

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Upholstery
Crafts
Light paneling
Home project applications

INCLUDES

US100 Upholstery/Craft Stapler

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

SPECIFICATIONS

Part No. US-100

Weight: 2.8 lbs

Height: 9-1/2"

Length: 12-1/2"

Nail Capacity: 100

Nail Range: 3/8" - 9/16"

Nail Type: 22 Gauge Upholstery

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.

HP100 Headless Pin Nailer

Compact
lightweight
design



DESCRIPTION/SUGGESTED SPECIFICATIONS

HP100 Headless Pin Nailer—

COMPACT – LIGHTWEIGHT.

Multi-directional exhaust port. Pin nails leave a very small hole for easy finishing and painting.

FAST



LIGHTWEIGHT



PROFESSIONAL



ADVANTAGES

■ Quick release nose piece

■ Drives 1/2" to 1-1/2" pin nails

SELECTION CHART

23 Gauge Pin Nails

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK
1"	0.025	Chisel	23	Brite	323001	3,000
3/4"	0.025	Chisel	23	Brite	323034	3,000
1-1/2"	0.025	Chisel	23	Brite	323112	3,000
1-3/8"	0.025	Chisel	23	Brite	323138	3,000

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



Fine woodworking and trim work

INCLUDES

- HP100 Headless Pin Nailer
- Safety glasses
- Tool case
- Allen wrench and oil

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

SPECIFICATIONS

Part No. HP100

Weight: 1.2 lbs

Height: 9-1/4"

Length: 7-3/4"

Nail Capacity: 100

Nail Range: 1/2" - 1-1/2"

Magazine Angle: Straight

Nail Type: 23 Gauge - Smooth,
Galvanized Pin Nails

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts,
6-month limited on magazine parts,
1-year limited on housing and cap parts.

Positive Placement PF250S

**Dependable,
Lightweight,
Compact and
Accurate**



APPLICATIONS



Joist Hangers

INCLUDES

Positive Placement PF250S
Safety Glasses
Owner's Manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

Positive Placement Tool—

DESIGNED FOR PROFESSIONAL FRAMERS

Paslode is proud to introduce the latest customer-backed innovation. The Paslode® 21Ž2" Positive Placement® Metal Connecting System is designed to provide installers the optimal way for fastening structural hardware to wood structures. The pneumatic system significantly reduces installation time, allowing jobs to be completed faster and reducing the need for additional labour.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- Versatile: Drives 1 ½" and 2 ½" nails.
- Dependable: Drive nails consistently to maximize productivity and efficiency.
- Lightweight and Compact: Reduces fatigue and increases maneuverability.
- Accurate: Probing tip guides nails into hardware holes.

SELECTION CHART

30 Degree Positive Placement Nails

LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.148	Smooth	30	Galvanized	650014	3,000
1-1/2"	0.148	Smooth	30	Brite	650646	1,000
2-1/2"	0.148	Smooth	30	Brite	650027	2,500

- Mechanically Galvanized, premium corrosion protection with code recognition. Recognized for use in ACQ, MCQ and all pressure treated lumber.
- Heat Treated nails to improve drive performance and reduce bending
- ICC-ES Recognized, ESR-2126, ESR-3326, Galvanization meets ASTM B695 Class 55
- Patented Paper Tape Collation formula provides clean shear for consistent drive performance. Maintains Strip integrity when in contact with moisture and will not fall apart when dropped

SPECIFICATIONS

Part No. 511800

Weight: 7.8 lbs
Height: 14"
Length: 17.4"
Nail Capacity: 55-60 Nails (2 strips)
Nail Range: .131" to .162" (Shank)

Magazine Angle: 30 Degrees

Nail Type: 1-1/2" to 2-1/2" Positive Placement Hanger Nails – Brite and Galvanized

Air req: 80-120 PSI

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts

Floormaster Plus™

Floormaster Plus™ 2 in 1 Flooring Nailer/Stapler



DESCRIPTION/SUGGESTED SPECIFICATIONS

2 in 1 Flooring Nailer/Stapler—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance and solid reliability. Easy maintenance and low cost of ownership. Lightweight – 10.4 lbs

PRECISE



FAST



POWERFUL



ADVANTAGES

- Easy Actuation
 - Only 4 lbs of pressure anywhere on poppet valve
 - Compact all-around striking surface to avoid marking/damaging walls
- Industry-Best Design & Ergonomics
 - Reverse handle with foam grip for reduced fatigue
 - Compact size for nailing boards closer to the end walls

SELECTION CHART

Flooring Staples and Cleats

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK	NAILS PER BOX
1-3/4"	Staple	Chisel	15	Brite	151134	1,000	5,000
2"	Staple	Chisel	15	Brite	151002	1,000	5,000
2"	Cleat	Cleat	16	Brite	100002	1,000	

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS



3/4" Hardwood flooring



INCLUDES

Tool & Mallet

SPECIFICATIONS

Part No. F2N1-200

Weight: 10.4 lbs

Height: 18"

Length: 16"

Flooring Fasteners: 15GA staples & 16GA L-cleats

Fastener Lengths: 1-3/4", 2" 15GA staples & 2" 16 GA L-cleats

FloorMaster Pro™

Floormaster Pro™ Nailer/Stapler 2 in 1 Combo



INCLUDES

Tool & Mallet

DESCRIPTION/SUGGESTED SPECIFICATIONS

Nailer/Stapler 2 in 1 Combo—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance, unfailing reliability. Ideal for flooring professionals, small contractors and self-employed installers.

PRECISE



SPEED



POWERFUL



ADVANTAGES

- Easy firing pneumatic valve
- Long lasting valve inside
- Light impact all-around striking cap
- Requires only a few drops of non-detergent oil weekly for lubrication

SELECTION CHART

Flooring Staples and Cleats

LENGTH	SHANK DIAMETER	SHANK TYPE	GAUGE	COATING	PRODUCT NUMBER	NAILS PER PACK	NAILS PER BOX
1-3/4"	Staple	Chisel	15	Brite	151134	1,000	5,000
2"	Staple	Chisel	15	Brite	151002	1,000	5,000
2"	Cleat	Cleat	16	Brite	100002	1,000	

- ICC-ES Recognized, ESR-1539
- Code approved for use in pressure treated lumber in accordance with ASTM A 153

APPLICATIONS

1/2" to 3/4" Solid and Engineered Flooring



SPECIFICATIONS

Part No. FNS-200

Weight: 11 lbs

Height: 21-5/8"

Length: 18"

Flooring Fasteners: 15-1/2ga staples
& 16ga L-Cleats

Fastener Lengths: 2", 1-3/4", 1-1/2"

Miscellaneous Fasteners

SELECTION CHART

MISCELLANEOUS FASTENERS

18 Gauge Flooring Cleats

LENGTH	TYPE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	CLEATS PER PACK
2"	Cleat	Chisel	18	Brite	150018	1,000

15 Degree Coil Nails

LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
2"	0.099	Spiral	15	Brite	404582	4,500
2-1/4"	0.099	Spiral	15	Brite	404583	4,500
2-1/2"	0.099	Spiral	15	Brite	404584	4,500
3"	0.12	Spiral	15	Brite	404508	4,500
3-1/4"	0.12	Spiral	15	Brite	404510	4,500

18 Gauge GEN-ER-X 7/32" Crown Staples

LENGTH	TYPE	STAPLE POINT	GAUGE	COATING	PRODUCT NUMBER	STAPLES PER PACK
5/8"	7/32"	Chisel	18	Galvanized	732058	5,000
1"	7/32"	Chisel	18	Galvanized	732001	5,000
1-3/8"	7/32"	Chisel	18	Galvanized	732138	5,000

National Headquarters

120 Travail Road
Markham, Ontario, L3S 3J1

Tel: 905-471-7403
800-387-9692

Fax: 905-471-7208
800-668-8688

Technical and Customer Service Support

Tel: 800-387-9692

Fax: 800-668-8688

Regional Warehouses

- Markham, Ontario
- Coquitlam, British Columbia
- Calgary, Alberta

Take Advantage of these Contractor Services from ITW Construction Products Canada

From job sites to engineering firms, from Safety Seminars to on-site services, we hope you take advantage of our many contractor services—at no charge! After all, it's one thing to offer the quality products you need to do your job. It's another to provide you with superior service, engineering expertise and total product support.

At ITW Construction Products Canada, we are proud of the partnerships we have built through the years with our distributor network and contractors. Thanks to quality products, innovative services and on-time delivery, we will continue to build new relationships and strengthen existing ones today... and into the next century.

- Factory representatives with years of training and service experience will go out to your job site to provide you with product, service and technical assistance.
- We provide architects and engineers with complete submittal packages which gives them the technical data needed to specify ITW Construction Products Canada products. Contact your ITW Construction Products Canada Distributor or your nearest Customer Service location to request submittal packages.

Technical Application Assistance:

- Our staff of application specialists are ready to assist you with any type of application or code approval question during any phase of your project. Call 1-800-387-9692 between 8:00 a.m. and 5:00 p.m. EST, Monday through Friday.

Distributed By



The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.

Ramset, T4, T3, T3Cup, Trakfast, GypFast, Mastershot, Triggershot, Hammershot, PowerPoint, TE Pin and Climacoat are trademarks of Illinois Tool Works, Inc.

A7+, C6+, Dynabolt, G5, Hammer-Set, LDT, Multi-Set II, Poly Set, Red Head, Redi-Drive, S7, Striker, and Trubolt are trademarks of ITW Red Head and Illinois Tool Works, Inc.

Teks, TruGrip GT, Scots, Maxiseal, Dek-Cap, Tapcon, SG, Tapcon, Maxi-Set Tapcon, Condrive, E-Z Ancor, E-Z Toggle, Twist-N-Lock, E-Z Lite, E-Z Mini, Stud Solver, Hi-Lo, S-12, Backer-On, Rock-On, Decking, Dec-U-Drive, Dek-Cap, Grid-Mate, Grid-Mate, PB, Climaseal, Spex, Climacoat, UltraShield, Climashield and Building Ideas That Work are trademarks of ITW Buildex and Illinois Tool Works, Inc.

Sammys, Sammy X-Press, Sammy X-Press It, Sammy X-Press Swivel, Sammy X-Press Sidewinder, Tapcon, Sammy Saddle, Speedy Pole Tool, Spot-Rite Level, and Truss-T Hanger are trademarks of ITW Buildex and Illinois Tool Works, Inc.

The term "Paslode" is a trademark and the Paslode logo and all related product and service names, designs and slogans are Paslode trademarks. Paslode, RounDrive, Impulse, Positive Placement are registered trademarks, PowerFramer and quicklode are trademarks of Illinois Tool Works.

R4, RSS, Kameleon, Fin/Trim, RT Composite, Low Profile Cabinet, Pheinox, Top Star, VWS, Caliburn, and The GRK Fasteners Canada Ltd. and all associated designs and logos are trademarks of GRK Fasteners Canada Ltd., used under license.

Hilti is a registered trademark of Hilti, Corp.

DensGlass is a registered trademark of Georgia Pacific Building Products.

Dekstrip, Dektite, Retrofit Dektite, and Dektite are registered trademarks of Deks Industries Pty Ltd.

Phillips Square-drive is a registered trademark of the Phillips Screw Company.