

# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 02-18-2026 Revision date: 02-18-2026 Version: 1.0

### SECTION 1 Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : Paslode 6V NiCd Battery  
Product code : Not available

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Battery

#### 1.4. Supplier's details

##### Supplier

ITW Construction Products Canada  
120 Travail Road  
Markham, ON, L3S 3J1  
T 905-471-7403

#### 1.5. Emergency phone number

Emergency number : CANUTEC 24-hour number (613-996-6666).

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

This product is a manufactured article. GHS classification and labeling are not applicable to product in purchased form. The hazards indicated in this document apply only when this product is cut, drilled, or modified in such a way that electrolyte is released.

##### Classification (GHS CA)

Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 4	H312	Harmful in contact with skin.
Acute toxicity (inhalation:dust,mist), Category 2	H330	Fatal if inhaled.
Skin irritation, Category 2	H315	Causes skin irritation.
Respiratory sensitization, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Germ cell mutagenicity, Category 1B	H340	May cause genetic defects.
Carcinogenicity, Category 1A	H350	May cause cancer.
Reproductive toxicity, Category 1B	H360	May damage fertility.
Specific target organ toxicity, Repeated exposure, Category 1	H372	Causes damage to organs (kidneys, bone) through prolonged or repeated exposure.

#### 2.2. GHS label elements, including precautionary statements

##### GHS CA labelling

Hazard pictograms (GHS-CA) :



# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Signal word (GHS CA)	: Danger
Hazard statements (GHS-CA)	: H302+H312 - Harmful if swallowed or in contact with skin H315 - Causes skin irritation H317 - May cause an allergic skin reaction H330 - Fatal if inhaled H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled H340 - May cause genetic defects. H350 - May cause cancer. H360 - May damage fertility or the unborn child H372 - Causes damage to organs (kidneys, bone) through prolonged or repeated exposure.
Precautionary statements (GHS-CA)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust, fume, gas, mist, vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P284 - Wear respiratory protection. P308+P313 - IF exposed or concerned: Get medical advice or attention. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 - Immediately call a POISON CENTER or a doctor. P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell. P330 - Rinse mouth. P302+P352 - IF ON SKIN: Wash with plenty of water. P362+P364 - Take off contaminated clothing and wash it before reuse. P333+P313 - If skin irritation or rash occurs: Get medical advice or attention. P312 - Call a POISON CENTER or a doctor if you feel unwell. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity

77% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

13% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Nickel	Nickel metal / Nickel, elemental / Nickel, metallic / Nickel, metal / C.I. 77775 / Nickel (Metallic) / Nickel catalyst, dry	CAS-No.: 7440-02-0	10 – 30
Cadmium	Cadmium, elemental / Cadmium metal / C.I. 77180 / Cadmium (non-pyrophoric) / Cadmium (pyrophoric)	CAS-No.: 7440-43-9	10 – 30
Cadmium hydroxide (Cd(OH) <sub>2</sub> )	Cadmium hydroxide / Cadmium dihydroxide / cadmium hydroxide	CAS-No.: 21041-95-2	10 – 30
Nickel hydroxide (Ni(OH) <sub>2</sub> )	Nickel dihydroxide / Nickel(II) hydroxide / Nickel(2+) hydroxide / Nickelous hydroxide / Nickel hydroxide	CAS-No.: 12054-48-7	5 – 30

\*Chemical name, CAS number and/or exact concentration have been withheld as CBI

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Not applicable for product in finished form. . Inhalation of material from a sealed battery is not expected to be a route of exposure. If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
First-aid measures after skin contact	: Not applicable for product in finished form. . IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Not applicable for product in finished form. . IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Not applicable for product in finished form. . IF SWALLOWED: Rinse mouth. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: Fatal if inhaled. May cause irritation to the respiratory tract. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapours or mists from a ruptured battery may cause respiratory irritation.
Symptoms/effects after skin contact	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: May cause an allergic skin reaction. Harmful in contact with skin. Skin contact with a ruptured battery can cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: Eye contact with the contents of a ruptured battery can cause severe irritation to the eye. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after ingestion	: Not applicable for product in finished form. Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

## SECTION 5 Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors. Irritating vapours. Toxic gases.
-------------	--

### 5.3. Special protective actions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
Environmental precautions	: Prevent entry to sewers and public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Pick up large pieces, then place in a suitable container. Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not short circuit, puncture, incinerate, crush, immerse in water, or expose to temperatures outside the temperature range stipulated by the manufacturer for the product. If this occurs, electrolyte leakage, or battery vent/explosion/fire may also occur depending on the circumstances. Do not use if battery is showing signs of damage or wear. Do not mix batteries of different types and brands. Do not mix new and used batteries. Avoid deep discharge of the battery.
- Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Protect from moisture. Store in a dry, cool and well-ventilated place. Store at room temperature. Store locked up. Keep away from heat and direct sunlight.
- Storage temperature : 5 – 20 °C

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

<b>Nickel (7440-02-0)</b>	
<b>USA - ACGIH® - Threshold Limit Values</b>	
ACGIH® TLV® TWA	1.5 mg/m <sup>3</sup> (inhalable particulate matter)
ACGIH® chemical category	Not Suspected as a Human Carcinogen
<b>USA - ACGIH® - Biological Exposure Indices</b>	
BEI	5 µg/l Parameter: Nickel - Medium: urine - Sampling time: post-shift at end of workweek (background)
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Nickel
OSHA PEL TWA	1 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Cadmium (7440-43-9)</b>	
<b>USA - ACGIH® - Threshold Limit Values</b>	
ACGIH® TLV® TWA	0.01 mg/m <sup>3</sup> 0.002 mg/m <sup>3</sup> (respirable particulate matter)
ACGIH® chemical category	Suspected Human Carcinogen
<b>USA - ACGIH® - Biological Exposure Indices</b>	
BEI	5 µg/g creatinine Parameter: Cadmium - Medium: urine - Sampling time: not critical (background) 5 µg/l Parameter: Cadmium - Medium: blood - Sampling time: not critical (background)
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	5 µg/m <sup>3</sup>

# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Cadmium (7440-43-9)	
OSHA PEL C	0.3 mg/m <sup>3</sup> (applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect-fume) 0.6 mg/m <sup>3</sup> (applies to any operations or sectors for which the Cadmium standard is stayed or otherwise not in effect-dust)
Remark (OSHA)	Cadmium is subject to the standard 29 CFR 1910.1027 and 1926.1127, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

<b>Hand protection:</b>
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

<b>Eye protection:</b>
Safety glasses or goggles are recommended when using product.

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Respiratory protection:</b>
Wear respiratory protection. [In case of inadequate ventilation] wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. In case of insufficient ventilation, wear suitable respiratory equipment. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: No data available
Colour	: No data available
Odour	: Odourless
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

### Nickel (7440-02-0)

Vapour pressure	1 mm Hg (at 1810 °C)
Particle characteristics	No data available

### Cadmium (7440-43-9)

Boiling point	765 °C
Vapour pressure	1.33 hPa (at 394 °C)
Particle characteristics	No data available

### Cadmium hydroxide (Cd(OH)<sub>2</sub>) (21041-95-2)

Particle characteristics	No data available
--------------------------	-------------------

### Nickel hydroxide (Ni(OH)<sub>2</sub>) (12054-48-7)

Auto-ignition temperature	400 °C
Particle characteristics	No data available

## 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Extremely high or low temperatures. Humidity. Incompatible materials.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon.
Hardening time:	: No additional information available

## SECTION 11 Toxicological information

### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Inhalation:dust,mist: Fatal if inhaled.

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Paslude 6V NiCd Battery	
ATE CA (oral)	1295.828 mg/kg bodyweight
ATE CA (Dermal)	1721.739 mg/kg bodyweight
ATE CA (dust,mist)	0.097 mg/l/4h
Unknown acute toxicity (GHS CA)	77% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 13% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg (Source: EU_RAR)
LC50 inhalation rat	> 10.2 mg/l (Exposure time: 1 h Source: EU_RAR)

Cadmium (7440-43-9)	
LD50 oral rat	1140 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	25 mg/m <sup>3</sup> (Exposure time: 30 min Source: NLM_CIP)
ATE CA (oral)	1140 mg/kg bodyweight
ATE CA (Gases)	10 ppmv/4h
ATE CA (vapours)	0.025 mg/l/4h
ATE CA (dust,mist)	0.025 mg/l/4h

Cadmium hydroxide (Cd(OH) <sub>2</sub> ) (21041-95-2)	
ATE CA (oral)	500 mg/kg bodyweight
ATE CA (Dermal)	1100 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Nickel hydroxide (Ni(OH) <sub>2</sub> ) (12054-48-7)	
LD50 oral rat	1515 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	1200 mg/m <sup>3</sup> (Exposure time: 4 h Source: NLM_CIP)
ATE CA (oral)	1515 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	1.2 mg/l/4h
ATE CA (dust,mist)	1.2 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

Nickel (7440-02-0)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Cadmium (7440-43-9)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
<b>Cadmium hydroxide (Cd(OH)<sub>2</sub>) (21041-95-2)</b>	
IARC group	1 - Carcinogenic to humans
<b>Nickel hydroxide (Ni(OH)<sub>2</sub>) (12054-48-7)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity	: May damage fertility.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Causes damage to organs (kidneys, bone) through prolonged or repeated exposure.
<b>Nickel (7440-02-0)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
<b>Cadmium (7440-43-9)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
<b>Cadmium hydroxide (Cd(OH)<sub>2</sub>) (21041-95-2)</b>	
STOT-repeated exposure	Causes damage to organs (kidneys, bone) through prolonged or repeated exposure.
<b>Nickel hydroxide (Ni(OH)<sub>2</sub>) (12054-48-7)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
<b>Cadmium (7440-43-9)</b>	
Viscosity, kinematic	> 58.14 mm <sup>2</sup> /s
Symptoms/effects after inhalation	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: Fatal if inhaled. May cause irritation to the respiratory tract. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapours or mists from a ruptured battery may cause respiratory irritation.
Symptoms/effects after skin contact	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: May cause an allergic skin reaction. Harmful in contact with skin. Skin contact with a ruptured battery can cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Not applicable for product in finished form. If exposure to leaking electrolyte from ruptured or leaking battery occurs: Eye contact with the contents of a ruptured battery can cause severe irritation to the eye. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: Not applicable for product in finished form. Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye. Risk of exposure only occurs if the battery cell is mechanically, thermally, or electrically abused and the enclosure is compromised. If this occurs, exposure to electrolyte solutions contained in the battery cell may occur by inhalation, eye contact, skin contact, or ingestion.

# Paslode 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 12 Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

<b>Nickel (7440-02-0)</b>	
LC50 - Fish [1]	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio Source: IUCLID)
LC50 - Fish [2]	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static] Source: EPA)
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	0.18 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [1]	0.174 – 0.311 mg/l (Species: Pseudokirchneriella subcapitata [static])

<b>Cadmium (7440-43-9)</b>	
LC50 - Fish [1]	0.003 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)
LC50 - Fish [2]	0.006 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	0.0244 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

<b>Paslode 6V NiCd Battery</b>	
Persistence and degradability	Not established.

<b>Nickel (7440-02-0)</b>	
Persistence and degradability	Rapidly degradable

<b>Cadmium (7440-43-9)</b>	
Persistence and degradability	Rapidly degradable

<b>Cadmium hydroxide (Cd(OH)<sub>2</sub>) (21041-95-2)</b>	
Persistence and degradability	Rapidly degradable

<b>Nickel hydroxide (Ni(OH)<sub>2</sub>) (12054-48-7)</b>	
Persistence and degradability	Rapidly degradable

#### 12.3. Bioaccumulative potential

<b>Paslode 6V NiCd Battery</b>	
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : Not classified.

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Other information : No other effects known.

Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Do not remove as household garbage. Refer to manufacturer/supplier for information on recovery/recycling.

Additional information : When battery is to be disposed of, isolate the battery's positive (+) and negative (-) terminals to avoid these terminals from touching each other.

Ecological waste information : Hazardous waste due to toxicity.

### SECTION 14 Transport information

In accordance with TDG

#### 14.1. UN Number

UN-No. (TDG) : Not regulated

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (TDG) : Not regulated

#### 14.3. Transport hazard class(es)

##### TDG

Transport hazard class(es) (TDG) : Not regulated

#### 14.4. Packing group, if applicable

Packing group (TDG) : Not regulated

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

##### TDG

Not regulated

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

### SECTION 15 Regulatory information

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### SECTION 16 Other Information

Issue date : 02-18-2026

Revision date : 02-18-2026

Other information : None.

# Paslude 6V NiCd Battery

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Prepared by

: Nexreg Compliance Inc.

[www.Nexreg.com](http://www.Nexreg.com)



Full text of hazard classes and H-statements:	
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H340	May cause genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet (SDS), Canada - Nexreg 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.