

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 02-18-2026 Revision date: 02-18-2026 Version: 1.0

SECTION 1 Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : Paslude Pneumatic Lubricating oil
Product code : 403720

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricator/antifreeze

1.4. Supplier's details

Supplier

ITW Construction Products Canada
120 Travail Road
Markham, ON, L3S 3J1
T 905-471-7403

1.5. Emergency phone number

Emergency number : CANUTEC 24-hour number (613-996-6666).

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids, Category 3	H226	Flammable liquid and vapour.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

2.2. GHS label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS-CA) : H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS-CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

P331 - Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P370+P378 - In case of fire: Use Carbon dioxide (CO2). Water spray or fog. foam. Dry chemical. to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based / Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15-30 and produces a finished oil with a viscosity of approximately 15cSt at 40°C. It contains a relatively large proportion of saturated hydrocarbons.)	CAS-No.: 72623-86-0	45 - 70

Paslode Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Petroleum distillates, hydrotreated light	Distillates (petroleum), hydrotreated light; Kerosine — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 oC to 290 oC (302 oF to 554 oF).] Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Kerosene / c13-14 isoparaffin / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) / Light Aliphatic Hydrocarbon / Odourless light petroleum hydrocarbons / Distillates (petroleum), hydro-treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] / Distillates, petroleum, hydrotreated light / Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	7 - 13

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

Pasode Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash clothing before re-using. Get medical attention if irritation develops and persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or a doctor.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO ₂). Water spray or fog. foam. Dry chemical.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour. Products of combustion may include, and are not limited to: oxides of carbon. Harmful vapours
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.
Environmental precautions	: Prevent entry to sewers and public waters.

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.
- Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.
- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

USA - ACGIH® - Threshold Limit Values

Local name	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
ACGIH® TLV® TWA	5 mg/m ³
ACGIH® TLV® STEL	10 mg/m ³
OSHA PEL	Not available
OSHA PEL STEL	Not available
NIOSH REL	Not available

Lubricating oils (petroleum), C15 -30, hydrotreated neutral oil-based

USA - ACGIH® - Threshold Limit Values

Local name	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
ACGIH® TLV® TWA	5 mg/m ³
ACGIH® TLV® STEL	10 mg/m ³
OSHA PEL	5 mg/m ³
OSHA PEL STEL	10 mg/m ³
NIOSH REL	Not available

Paslode Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
Hydrotreated light petroleum distillates	
USA - ACGIH® - Threshold Limit Values	
Local name	Hydrotreated light petroleum distillates
ACGIH® TLV® TWA	200 ppm
ACGIH® TLV® STEL	500 ppm
OSHA PEL	200 ppm
OSHA PEL STEL	500 ppm
NIOSH REL	Not available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : Yellow
Odour : Mild
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : No data available
Freezing point : No data available

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Boiling point	: 160 °C
Flash point	: 40 °C Tag closed cup
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.86
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: Lower explosion limit: 0.8 Upper explosion limit: 6
Particle characteristics	: No data available

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)	
Boiling point	207 – 750 °C (at 1013.25 hPa)
Flash point	(>115 - <=268 °C - open cup)
Vapour pressure	< 0.1 hPa Temp.: 20 °C
Particle characteristics	No data available

Petroleum distillates, hydrotreated light (64742-47-8)	
Boiling point	146 – 299 °C Atm. press.: 101,325 kPa
Flash point	29 – 70 °C Atm. press.: 101,325 kPa
Auto-ignition temperature	> 200 °C (at 1013 hPa)
Vapour pressure	0.01 – 0.3 hPa (at 20 °C)
Particle characteristics	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions. May form flammable/explosive vapour-air mixture.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Sources of ignition. Direct sunlight. Incompatible materials.
Incompatible materials	: Strong oxidizers.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. May release flammable gases.; Toxic fumes
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 2000 mg/kg (Source: IUCLID)
LC50 inhalation rat	2.18 mg/l/4h
ATE CA (vapours)	2.18 mg/l/4h
ATE CA (dust,mist)	2.18 mg/l/4h

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 2000 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	> 5.2 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	-------------------------------------------------------------------

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Hazardous to the aquatic environment, short-term (acute) : Not classified.

Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)

12.2. Persistence and degradability

Paslude Pneumatic Lubricating oil	
Persistence and degradability	Not established.
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Rapidly degradable
Petroleum distillates, hydrotreated light (64742-47-8)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Paslude Pneumatic Lubricating oil	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF - Fish [1]	61 – 159

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.
Other information : No other effects known.
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14 Transport information

In accordance with TDG

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

14.1. UN Number

UN-No. (TDG) : UN1268

14.2. UN Proper Shipping Name

Proper Shipping Name (TDG) : PETROLEUM DISTILLATES, N.O.S. (hydrotreated light petroleum distillates)

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 3

Hazard labels (TDG) : 3



14.4. Packing group, if applicable

Packing group (TDG) : III

14.5. Environmental hazards

Dangerous for the environment : No

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

TDG

UN-No. (TDG) : UN1268

TDG Special Provisions : 91 - Repealed, SOR/2017-137,92 - (1) The consignor must classify these dangerous goods on the basis of samples.
(2) The consignor must make available to the Minister, on reasonable notice given by the Minister, a document that explains the sampling method and includes the following information:
(a) the scope of the method;
(b) the sampling apparatus;
(c) the sampling procedures;
(d) the frequency and conditions of sampling; and
(e) a description of the quality control management system in place, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).

Explosive Limit and Limited Quantity Index : 5 L

Excepted quantities (TDG) : E1

Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Paslude Pneumatic Lubricating oil

Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 16 Other Information

Issue date : 02-18-2026
Revision date : 02-18-2026

Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of hazard classes and H-statements:

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways

Safety Data Sheet (SDS), Canada - Nexreg 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.