

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 03-24-2026 Revision date: 03-24-2026 Version: 1.0

### SECTION 1 Identification

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : Tapcon Blue Climaseal  
Product code : WRA-202A

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : **NEED**

#### 1.4. Supplier's details

##### Supplier

ITW Construction Products Canada  
120 Travail Road  
Markham, ON, L3S 3J1  
T 905-471-7403

#### 1.5. Emergency phone number

Emergency number : CANUTEC 24-hour number (613-996-6666).

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Acute toxicity (inhalation:vapour), Category 4	H332	Harmful if inhaled.
Skin irritation, Category 2	H315	Causes skin irritation.
Eye irritation, Category 2A	H319	Causes serious eye irritation.

#### 2.2. GHS label elements, including precautionary statements

##### GHS CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Warning

Hazard statements (GHS-CA) : H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled

Precautionary statements (GHS-CA) : P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, eye and face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P332+P313 - If skin irritation occurs: Get medical advice or attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER or a doctor if you feel unwell.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice or attention.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity

25% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
2-butoxyethanol	2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol	CAS-No.: 111-76-2	5 - 10
2-Butanol	sec-Butyl alcohol / sec-Butanol / s-Butyl alcohol / 2-Hydroxybutane / 1-Methyl-1-propanol / Methylenebutylcarbinol / Butanol, 2-	CAS-No.: 78-92-2	1 - 5
Diethylene glycol monobutyl ether	Butoxydiglycol / Butyl carbitol / Butyl dioxitol / Diethylene glycol butyl ether / Ethanol, 2-(2-butoxyethoxy)- / 2-(2-butoxyethoxy)ethanol / Diethylene glycol mono-n-butyl ether / BUTOXYDIGLYCOL	CAS-No.: 112-34-5	1 - 5
2-(Dimethylamino)ethanol	Dimethylaminoethanol / N,N-Dimethylethanolamine / Dimethylethanolamine / Ethanol, 2-(dimethylamino)- / Ethanol, 2-dimethylamino- / Ethanolamine, N,N-dimethyl-	CAS-No.: 108-01-0	1 - 5

Comments

:\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

### SECTION 5 Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Alcohol foam.
Unsuitable extinguishing media	: Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours.
-------------	---

#### 5.3. Special protective actions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
Environmental precautions	: Prevent entry to sewers and public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

2-butoxyethanol (111-76-2)	
<b>USA - ACGIH® - Threshold Limit Values</b>	
Local name	2-Butoxyethanol (EGBE)
ACGIH® TLV® TWA	49 mg/m <sup>3</sup>
ACGIH® TLV® TWA	10 ppm
ACGIH® TLV® STEL	196 mg/m <sup>3</sup>
ACGIH® TLV® STEL	40 ppm
Remark (ACGIH®)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH® chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2025
<b>USA - ACGIH® - Biological Exposure Indices</b>	
Local name	2-Butoxyethanol (EGBE)
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m <sup>3</sup>
OSHA PEL TWA	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>2-Butanol (78-92-2)</b>	
<b>USA - ACGIH® - Threshold Limit Values</b>	
ACGIH® TLV® TWA	100 ppm
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	450 mg/m <sup>3</sup>

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

2-Butanol (78-92-2)	
OSHA PEL TWA	150 ppm
Diethylene glycol monobutyl ether (112-34-5)	
USA - ACGIH® - Threshold Limit Values	
Local name	Diethylene glycol monobutyl ether
ACGIH® TLV® TWA	67.5 mg/m <sup>3</sup> (IFV - Inhalable fraction and vapor)
ACGIH® TLV® TWA	10 ppm (inhalable fraction and vapor)
Remark (ACGIH®)	TLV® Basis: Hematologic, liver & kidney eff
Regulatory reference	ACGIH 2025

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

<b>Hand protection:</b>
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

<b>Eye protection:</b>
Wear eye/face protection

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: moderate. Viscosity. Liquid.
Colour	: No data available
Odour	: Characteristic Water-based paints
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Boiling point	: 98 – 230 °C (208.4 - 446 °F)
Flash point	: 105 °C (221°F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable
Vapour pressure	: No data available
Relative vapour density at 20°C	: 3.82
Relative density	: No data available
Relative density of saturated gas/air mixture	: 1.137
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: LEL: 1.0; UEL: 25.0
Particle characteristics	: No data available

### 2-butoxyethanol (111-76-2)

Boiling point	(>171 - <171.5 °C - at 1 atm)
Flash point	67 °C (closed cup)
Auto-ignition temperature	230 °C
Vapour pressure	0.79 – 1.3 hPa (at 20 °C)
Particle characteristics	No data available

### 2-Butanol (78-92-2)

Boiling point	99.5 °C
Flash point	24 °C
Auto-ignition temperature	406 °C
Particle characteristics	No data available

### Diethylene glycol monobutyl ether (112-34-5)

Boiling point	230 °C
Flash point	105 °C (closed cup)
Auto-ignition temperature	227.78 °C
Vapour pressure	0.027 hPa (at 20 °C)
Particle characteristics	No data available

### 2-(Dimethylamino)ethanol (108-01-0)

Boiling point	134.1 °C (at 1013.25 hPa)
Flash point	31 °C (open cup)
Auto-ignition temperature	295 °C
Vapour pressure	4 mm Hg (at 20 °C)
Particle characteristics	No data available

## 9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 2.67 lb/gal

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 10 Stability and reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials.
Incompatible materials	: Strong oxidizers.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Oxides of nitrogen. Irritating vapors.
Hardening time:	: No additional information available

### SECTION 11 Toxicological information

#### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Inhalation:vapour: Harmful if inhaled.

Tapcon Blue Climaseal	
ATE CA (vapours)	15 mg/l/4h
Unknown acute toxicity (GHS CA)	25% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))
2-butoxyethanol (111-76-2)	
LD50 oral rat	1200 mg/kg
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rabbit	435 mg/kg (Source: OECD_SIDS)
LC50 inhalation rat	3 mg/l
LC50 inhalation rat	486 ppm/4h
ATE CA (oral)	1200 mg/kg bodyweight
ATE CA (Dermal)	435 mg/kg bodyweight
ATE CA (Gases)	486 ppmv/4h
ATE CA (vapours)	3 mg/l/4h
ATE CA (dust,mist)	3 mg/l/4h
2-Butanol (78-92-2)	
LD50 oral rat	2200 mg/kg (Source: JAPAN_GHS)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LD50 dermal rabbit	> 2000 mg/kg (Source: JAPAN_GHS)
ATE CA (oral)	2200 mg/kg bodyweight
Diethylene glycol monobutyl ether (112-34-5)	
LD50 oral rat	5660 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2700 mg/kg (Source: NLM_CIP)
ATE CA (oral)	5660 mg/kg bodyweight

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
ATE CA (Dermal)	2700 mg/kg bodyweight
<b>2-(Dimethylamino)ethanol (108-01-0)</b>	
LD50 oral rat	1803 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	1220 mg/kg (Source: NZ_CCID)
LC50 inhalation rat	1641 ppm/4h
ATE CA (oral)	1803 mg/kg bodyweight
ATE CA (Dermal)	1220 mg/kg bodyweight
ATE CA (Gases)	1641 ppmv/4h
ATE CA (vapours)	3 mg/l/4h
ATE CA (dust,mist)	0.5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
<b>2-(Dimethylamino)ethanol (108-01-0)</b>	
pH	11 – 12 (conc: 10 % (solution))
Serious eye damage/irritation	: Causes serious eye irritation.
<b>2-(Dimethylamino)ethanol (108-01-0)</b>	
pH	11 – 12 (conc: 10 % (solution))
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
<b>2-butoxyethanol (111-76-2)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified.
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
NOAEL (animal/male, F0/P)	> 452 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:
NOAEL (animal/female, F0/P)	> 470 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure	: Not classified.
<b>2-Butanol (78-92-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>2-(Dimethylamino)ethanol (108-01-0)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified.
<b>2-butoxyethanol (111-76-2)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
<b>Diethylene glycol monobutyl ether (112-34-5)</b>	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Diethylene glycol monobutyl ether (112-34-5)	
NOAEL (dermal, rat/rabbit, 90 days)	< 200 mg/kg bodyweight Animal: rat, Guideline: other., Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
2-(Dimethylamino)ethanol (108-01-0)	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard : Not classified.

Diethylene glycol monobutyl ether (112-34-5)	
Viscosity, kinematic	6.803 mm <sup>2</sup> /s
2-(Dimethylamino)ethanol (108-01-0)	
Viscosity, kinematic	40268.539 mm <sup>2</sup> /s

Symptoms/effects after inhalation : Harmful if inhaled. May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.  
Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.  
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12 Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
2-Butanol (78-92-2)	
LC50 - Fish [1]	3380 – 3990 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	1859 – 7143 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

2-Butanol (78-92-2)	
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Diethylene glycol monobutyl ether (112-34-5)	
LC50 - Fish [1]	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	> 100 mg/l (Species: Desmodesmus subspicatus)
2-(Dimethylamino)ethanol (108-01-0)	
LC50 - Fish [1]	81 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	98.77 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	35 mg/l (Species: Desmodesmus subspicatus)

### 12.2. Persistence and degradability

Tapcon Blue Climaseal	
Persistence and degradability	Not established.
2-butoxyethanol (111-76-2)	
Persistence and degradability	Rapidly degradable
2-Butanol (78-92-2)	
Persistence and degradability	Rapidly degradable
Diethylene glycol monobutyl ether (112-34-5)	
Persistence and degradability	Rapidly degradable
2-(Dimethylamino)ethanol (108-01-0)	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

Tapcon Blue Climaseal	
Bioaccumulative potential	Not established.
2-butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water	0.81 (at 25 °C (at pH 7))
2-Butanol (78-92-2)	
Partition coefficient n-octanol/water	0.6
Diethylene glycol monobutyl ether (112-34-5)	
BCF - Fish [1]	(no bioconcentration expected)
Partition coefficient n-octanol/water	1 (at 20 °C (at pH 7))
2-(Dimethylamino)ethanol (108-01-0)	
Partition coefficient n-octanol/water	-0.55 (at 23 °C)

### 12.4. Mobility in soil

No additional information available

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

### 12.5. Other adverse effects

Ozone : Not classified.  
Other information : No other effects known.  
Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### SECTION 14 Transport information

In accordance with TDG

#### 14.1. UN Number

UN-No. (TDG) : Not regulated

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (TDG) : Not regulated

#### 14.3. Transport hazard class(es)

**TDG**  
Transport hazard class(es) (TDG) : Not regulated

#### 14.4. Packing group, if applicable

Packing group (TDG) : Not regulated

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

**TDG**  
Not regulated

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

### SECTION 15 Regulatory information

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### SECTION 16 Other Information

Issue date : 03-24-2026  
Revision date : 03-24-2026  
Other information : None.

# Tapcon Blue Climaseal

## Safety Data Sheet

According to the Hazardous Products Regulations (HPR) WHMIS 2022

Prepared by

: Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



### Full text of hazard classes and H-statements:

H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

Safety Data Sheet (SDS), Canada - Nexreg 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.